having a neck, a lower-wire-segment, and an upper-wire-segment, said container comprising:

a bottom;

a continuous sidewall around the perimeter of said bottom;

at least one channel a retainer comprising two parallel vertical members connected to said bottom, said retainer further comprising two barriers, each said barrier extending perpendicularly from a respective vertical member, said barriers being connected to said bottom to there-between define a channel for holding a lower segment of a lure along said bottom; and barriers;

a first at least one catch in at least one of said vertical members for compressing an upper segment of the lure toward a lower segment of the lure to hold the lure stationary in the channel, above said bottom in each of said channels; and

a second catch spaced vertically from said first catch and positioned above said bottom in each of said channels;

whereby when said fishing lure is placed within said channel with said lower wire segment adjacent to said bottom, and said upper wire segment is placed within said oatch, said upper-wire segment is compressed toward said lower wire segment, and said fishing lure is held in place.

strip having a curved neck rest at a first end, said neck rest shaped to cradle said the neck of a lure, a strip, said strip having two ends, extending from said neck rest perpendicular to said lower wire segment, toward said upper wire segment; and a catch, said eatch positioned at said a second end of said strip opposite said neck rest, forming a C shape for compressing an upper lure segment toward a lower lure segment;

whereby when said the neck of a lure is placed in said neck rest, and said an upper wire lure segment is compressed and placed within said catch, the lure is compressed compression of said upper wire segment is maintained and said spinner bait is and held in place within said single piece body.

12. (Amended) A buzz bait insert for holding fishing lures, said fishing lures having a wire, said insert comprising: A container for holding fishing lures, comprising:

a bottom;

a continuous sidewall around the perimeter of said bottom;

an insert positioned within said continuous sidewall, said insert
comprising a rectangular floor having a first and second short side and a plurality
of pairs of buzz clips attached to said floor, each of said pairs of buzz clips
eriented aligned to open and close in a around a common line axis and encompass
a segment of a lure placed inside said buzz clips along said axis; and open along
said line

Respectfully submitted,

R. Brian Johnson

Registration No. 45,951